

#### **Corporate Headquarters**

#### North America Region:

#### **EMEA Region:**

Mijnwerkerslaan 34, 3550 Heusden-Zolder, Belgiun Oceania Region:

Asia Pacific Region:



Simplifed Touch Screen Solutions



## CONTENT


<ul> <li>Integrate touch screens seamlessly</li> </ul>	1 - 2
Simple touch screen extension	3 - 4
Multiple sources to a touch screen	5 - 8
<ul> <li>USB and video solution</li> </ul>	
− USB solution	
- Multi-view and control	
Multiple touch screens	9 - 10
Multi-format touch screen integration	11 - 12



## How to integrate touch screens seamlessly

- Have you heard about USB distance limitation?
  Usually USB 2.0 cannot go over 5m away, hence USB extender solutions.
- Are you looking to connect more than a single PC to a touch screen?

  Did you know, a KVM switch offers ease of switching and enables 3rd party integration.
- Push the limit with Networked AV
   The ideal solution for integrating multiple touch screens when connecting to a single or many computers.
- Looking for a turnkey solution for the meeting / classroom / training room? ATEN's presentation matrix switch with a built-in KVM switch is your ideal solution.





# Simple Touch screen Solutions



VE803
HDMI/USB CAT5 EXTENDER



VE8950 4K HDMI OVER IP



CE820 USB HDMI HDBASET 2.0 KVM EXTENDER



CE680 USB DVI Optical KVM Extender

## **Increase USB reach with ATEN KVM extenders**

Don't be limited to 5m away from a touch screen, ATEN offers a full range of KVM extenders that allows you to extend the distance between your console and the computer by up to 20KM. Ideal for touch screen installations such as classroom and hospital facilities.

#### **HDMI Equalizer**

**VE803** (1080p @40m) - Most cost effective option for USB and HDMI signal transmission

## HDMI Over IP


**VE8950** (4K @100m) - Multicast solution easy to deploy with a single cable in point to point

#### **HDMI over HDBaseT 2.0**

**CE820** (1080p @150m) - No compression and micro second latency in addition of long reach mode


#### **DVI over Fiber**

CE680 / CE690 (1920x1200 @600m/20km) EMI resistance for high secure and extra long transmission











4-port USB Boundless KM Switch



CS1822 | CS1824 2 / 4-Port USB 3.0 4K HDMI KVMP™ Switch



CM1284

4-Port USB 4K HDMI Multi-View KVMP™ Switch

## Share touch screen via HDMI and USB

All in one solution, perfect fit for meeting room and classroom applications. The ATEN CS1822 KVM Switch offers effortless management of two HDMI interface computers from a single USB keyboard, mouse and HDMI touch screen with the help of a built-in USB 3.1 Gen 1 hub.

#### Commands

Supports RS-232 serial commands

#### **Emulation**

USB Emulation for keyboard and mouse

#### USB 3.1 Gen 1 hub

USB 3.1 Gen 1 hub for an additional peripherals


#### **Superior video quality**

4096 x 2160 @ 60Hz and 3840 x 2160 @ 60Hz HDMI 2.0 compliant; HDCP 2.2 compliant

#### Video DynaSync™

Exclusive ATEN technology eliminates boot-up display problems and optimizes the resolution when switching among different sources

Power on detection



## Share touch screen via USB with multiple PC's

Integrate your touch screen solution smoothly with up to 4 computers. CS724KM offers external control via RS232 commands, in addition of 2 x USB 2.0 peripheral ports for touch screen and additional device.

#### Commands

Supports RS-232 serial commands

#### **Emulation**

USB Emulation for keyboard and mouse

#### **Port Selections**


Via front panel pushbutton, keyboard hotkey, mouse cursor, mouse wheel and RS-232

#### **Bus-Powered**

No external power adapter required

#### Compatibility

Compatible with Cat5 extender UCE60 to extend devices up to 60m



## Multi-view and control multi PC's via touch

With the help of the built-in toolbar, the CM1164A CM1284 offers a unique way to switch not only computer ports but also display layout from the touch screen.

#### Commands

Supports RS-232 serial commands

#### Multi-view console

Controls up to four video sources on one screen with display modes including Quad View, Picture in Picture (PiP), Picture by Picture (PbP), and Picture on Picture (PoP)


#### Video DynaSync™


Exclusive ATEN technology eliminates boot-up display problems and optimizes the resolution when switching among different sources

#### **Emulation**

USB Emulation for keyboard and mouse

#### Power on detection







## **VE8950 / VE8952 (POE) 4K HDMI OVER IP**

#### Networked AV

Connection	Video Over IP				
Video Interface	HDMI				
Model	VE8952T	VE8952R	VE8950T	VE8950R	
Inputs to Outputs	Multiple to Multiple		Multiple t	o Multiple	
Max. Resolution / Distance	4K@100m	4K@100m	4K@100m	4K@100m	
HDCP	1.4	1.4	1.4	1.4	
Audio	• (HDMI / Stereo)	• (HDMI / Stereo)	• (HDMI / Stereo)	• (HDMI / Stereo)	
RS-232 Channel				•	
IR Channel					
USB Channel					
Scaler	N/A		N/A		
POE			N/A	N/A	

## **Touch screen Matrix**

ATEN's Video over IP with touch screen capability delivers visually lossless 4K AV signals with low latency over long distance. VE8950/VE8952 is an ideal product for a wide range of environments, such as trade shows, airports, university campuses, conference centers, and shopping centers.

#### **Limitless Flexibility and Scalability**

Offering multi-functionality in extender, splitter, matrix switch, and video wall applications.

#### **Collaboration with ATEN Control System**

Directly operate VE8950R via CLI Telnet or RS-232 protocol from ATEN control system or 3rd Party

### Free Mobile App


Preview sources, control the Matrix with the tip of your finger

#### No additional server PCs or software

Manage your AV over IP system by loggingfrom the web GUI.

#### Go further for less with daisy chaining

Expand the AV network coverage and lowering costs per-port.



## **Multi-format Touch Screen** Integration Touch

PC PC PC PC



#### **VP1920**

#### 9 x 2 4K Presentation Matrix Switch

#### Ontional Accessories

Description	Part No. / Spec.	Page No.
HDMI Cable*	2L-7D02H-1 (2m) / 2L-7D03H (3 m)	11-5
HDBaseT Cat 6 Cable	2L-2910	11-1
Low Skew Cable	2L-2801	11-3
LockPro <sup>TM</sup> (HDMI Cable Lock)	2X-EA12	12-1
Full Range IR Receiver (30-56KHz)	2XRT-0003G-1	12-2
Full Range IR Emitter (30-56KHz)	2XRT-0004G	12-2
Network Switch	ES0152 / ES0152P	Altusen 3-34

<sup>\*</sup>Cables with different lengths are available

## **Enhance Interaction**

ATEN Presentation switch with touch screen capability is suitable for all small-to-medium sized corporate and education presentation environments, such as meeting rooms, classrooms, training rooms, or any other presentation setting, such as in exhibition centres or hotels.

#### **Compact device**

A compact device that consolidates multiple source formats and integrates easily with a digital podium


#### **Easy integration**

Easily integrates a touch panel into one system and mirrors the content to the projector screen

#### **De-clutter**

A simplified system by reducing the number of extra switches / converters / USB extenders

Matrix display mode VP1920 supports matrix display mode



Memo			